

Acknowledgment in Pictures and Switching Perceived Text Over Completely To Discourse

¹Amit Kumar, ¹Ashish Patel

¹Dept. of Computer Science & Engineering RDEC, Ghaziabad

Email- amit.kumar@gmail.com

Abstract — The main goal of this research is to foster a program that can recognize text characters from a normal picture and transform it into a voice signal. The program needs to do the indistinguishable activity for any transferred picture and PDF record. The application ought to likewise have tools for pace modulation, voice choosing options, and capacity ability for picture to message yield. The interest group for this program can be extended to incorporate individuals with extraordinary requirements who likewise have learning disabilities, small kids, and a few other cultural gatherings. The text is removed from the picture utilizing optical person acknowledgment (OCR), and the Windows Programming interface is used to transform the text into discourse. The programming language for advanced picture handling is MATLAB.

Keywords-- Digital image processing, optical character recognition, speech modulation, MSER Regions, stroke width algorithm, and image character recognition

1. INTRODUCTION

A famous area of PC innovation is picture to-discourse transformation. It lays out a urgent calculate how we draw in with the framework and connection points on numerous stages. It has for quite some time been an objective to repeat human capacities like perusing through machines. Machine perusing, notwithstanding, has created from a pipedream to reality during the past 50 years. The most successful type of human correspondence is in all probability discourse. One of the most popular uses of technologies in the fields of example acknowledgment and man-made consciousness is optical person acknowledgment.

The device helps with changing over printed data that is implanted in a picture or scene into discourse. This isn't the main use it could be put to. It is helpful to take text from PDF documents and transform it into discourse. The gathered text can be all put away as a text document in any area on the PC. While the text is being perused so anyone might hear, it likewise offers the choice to look into equivalents for words. Various speeds perhaps agreeable for clients to understand the language. Thus, a provision is added that takes into consideration discourse beat balance. Furthermore, clients can choose from different male and female speakers' voices as well as accents.

OCR, or optical person acknowledgment, is a procedure we use to remove text from photos. After that, a text-to-discourse (TTS) module transforms the text into sound. We can see that this procedure was split into two modules. The first is picture acknowledgment, and the second is discourse change for that image optical person acknowledgment. Optical person acknowledgment is alluded to as OCR. Through this methodology, the application will actually want to perceive a person naturally utilizing an optical method. OCR is the transformation of caught photos of printed or typewritten text into carefully variable data. Discourse union: Without straightforwardly utilizing a human voice, discourse blend makes discourse that is more human-like than mechanical. A voice synthesizer is, all the more as a general rule, kind of innovation that makes counterfeit discourse through the formation of images and signals. Altering the discourse's cadence has been conceivable. Furthermore, the application incorporates different voices and accents.

The above can be depicted by the following illustration:




Figure 1 An overview of the system

I. FRAMEWORK AND ARCHITECTURE

2.1) *HIGH LEVEL DESIGN*: THE HIGH LEVEL OPERATION OF THE SYSTEM IS DEPICTED IN THE DIAGRAM BELOW:

The graphic demonstrates that the system is made up of two primary modules:

The system's two primary components are depicted in the figure as:

- (a) image-to-text conversion and PDF generation
- (b) Conversion from text to speech

Image to Speech Conversion Using Digital Image Processing




Figure 2 High Level Diagram of the System

The conversion of a picture into speech is handled by these two modules. The text to speech module also includes a number of other features, such as word definitions and synonyms, pitch and tempo adjustments for speech output, and the ability to store extracted data as text files or in the.txt format.

2.2 *IMAGE/PDF TO TEXT CONVERSION*: THE DIAGRAM SHOWS THE VARIOUS

FUNCTIONALITIES OF THIS MODULE.




Figure 3 Detailed Diagram of Image/PDF to Text Conversion

The Image to Text Conversion module is further subdivided into three sub-modules that are in charge of Image to Text conversion.

- Capture an image
- Upload an image
- Upload a PDF file

The technique of extracting text from various sources differs. As seen in the illustration, word extraction from a taken image necessitates natural image processing. It begins by finding the text-containing portions of the picture. MSER (Maximally Stable Extremal Regions) and Stroke-Width algorithms are utilized to perform this as well as locate characters. The recognized letters are then combined into words and phrases using Optical Character Recognition (OCR). Finally, a text file with the extracted text is created.

The graphic below depicts this process:




Figure 4 Natural Image Processing for Captured Image

To improve efficiency, all noise in the image is clipped before to processing. The picture is then

OCR' d. The extracted text is subsequently written to a file in the working directory for further processing. The PDFBox.jar file is used to extract text from PDFs. It is integrated with the program to allow for smooth extraction from PDF files.

It is important to remember that the algorithms used to analyze natural images are designed in such a way that the quality of the image does not interfere with the precision with which the text is retrieved. The OCR works well enough for photos with non-straight text orientations and low resolution. In an image or a PDF, text can be in any font style and size. The algorithms have been designed to correctly recognize text in any style or size. When it is converted to text format, however, these details are lost because the algorithms are only equipped to read the text and not its font size and font style. The entire module has been designed to minimize latency and maximize efficiency.

2.2) *Text to Speech Conversion:* Text retrieved from any type of input is saved in the working directory as a text file. Microsoft supplies a Speech API that is utilized to supply different voices, and an algorithm is created to translate this text into speech.




Figure 5 Text to Speech Conversion Flowchart

The first image is taken, or, in the case of a PDF, it is uploaded. Using the prior module, text from the input is extracted and transformed to text

format. The text is then analyzed to divide into sentences.

These sentences must appear in the correct order alongside the voice output. When a full stop ("."), a question mark ("?"), or an exclamation mark ("!") is




Figure 6 Stroke Width Algorithm Flowchart

encountered, the text is broken into sentences. If Windows 32 SAPI is not available, the default configuration for the speech module is utilized. This module also allows users to alter the tempo and timing of their speech. A real-time play and pause feature is also available.

This module includes it. This module also includes highly useful features such as word definitions, which can be used offline because it is supported by the Microsoft Word API. The extracted text can be stored in any format for the user's future reference. Finally, this module allows the user to store the document in a variety of formats and easily access it for future reference.

2.3) *MSER Regions:* For blob detection in photos, the program uses the Maximally Stable Extreme Regions algorithm.

MSER changes with the picture threshold; given a threshold value, pixels below that threshold value are

"white," while those over or equal to that value are "black."

Because of the uniform color and great contrast of the text, the MSER feature detector performs well for locating text sections. The first step in constructing MSER is to execute

a basic luminance threshold of the picture by sweeping the intensity threshold from black to white. After that, the extracted related components

or Extreme Regions are executed. Following that, a threshold is determined when an external region is maximally stable. Finally, the descriptions of the areas as MSER features are acquired.

Although the MSER algorithm detects the majority of the text, it also detects several other stable regions in the image that are not text. The stroke width algorithm can assist in resolving this.

(2.5) *Stroke Width Algorithm:* This algorithm has been implemented to retrieve the most likely stroke containing the required pixel. The algorithm receives an RGB image and returns an image of the same size, where the regions of suspected text are marked.

The first step is the stroke width transform which is an operator which determines the width of the most likely stroke containing the pixel for each and every pixel. The output produced by the SWT is an image of the same size as the input image where each element contains the width of the stroke associated with that pixel. We have now obtained a map of the most likely stroke-widths for each pixel in the original image. The next step is to group all these pixels into letter candidates which is done by selecting two neighboring having similar stroke width, and then applying several rules to distinguish the letter candidates.

For this reason, we have modified the classical Connected Component algorithm by altering the association rule from a binary mask to a predicate which compares the SWT values of the pixels. To increase the efficiency and reliability we strive forward to group the letters. Since single letters are not expected to appear in images, closely positioned letter candidates are gathered together into regions of text.

(2.5) *Optical Character Recognition:* The method of translating text from a digital picture into editable text is known as optical

character recognition. It allows a machine to recognize the characters using optical methods.

The OCR result should preferably be the same as the input in formatting. The procedure begins with the picture file being pre-processed, followed by the acquisition of critical information about the textual text. MSER and the Stroke Width Algorithm aid in this process.

II. ALGORITHMS USE

(3.1) *Tokenization:* It's the process of breaking down the text into sentences and phrases. The work entails breaking down a text into smaller chunks (known as tokens) while discarding some characters, such as punctuation.

Consider the following example:

Text input: Potter walked to school yesterday.

Potter went to school yesterday, according to the text output.

The major disadvantage of this strategy is that it works better with some languages and worse with others. This is particularly true when it comes to tonal languages like Mandarin or Vietnamese.

Depending on the pronunciation, the Mandarin term *ma* can signify "a horse," "hemp," "a scold," or "a mother." The NLP algorithms are in grave danger.

(3.2) *Bag of Words:* This paradigm represents a text as a bag (multiset) of words, neglecting syntax and even word order while keeping multiplicity. In essence, the [bag of words](#) paradigm generates a matrix of incidence.

These word frequencies or instances are then employed as features in the training of a classifier.

Unfortunately, there are some drawbacks to this paradigm. The worst is the lack of semantic meaning and context, as well as the fact that such terms are not appropriately weighted (for example, in this model, the word "universe" weighs less than the word "they").

(3.3) *Text Summarization:* As the name

implies, NLP approaches can assist in the summarization of big volumes of text. Text summarization is commonly utilized in situations such as news headlines and research studies.

Text summarization can be done in two ways: extraction and abstraction. By deleting bits from the text, extraction methods create a rundown. Abstraction tactics produce summaries by constructing new text that conveys the essence of the original content.

Different NLP algorithms can be used for text summarization, such as Lex Rank, Text Rank, and Latent Semantic Analysis. To use Lex Rank as an example, this algorithm ranks sentences based on their similarity. Because more sentences are identical, and those sentences are identical to other sentences, a sentence is rated higher.

(3.4) *Lemmaization and Stemming*: Two of the strategies that assist us to develop a Natural Language Processing of the tasks are [lemmaization](#) and [stemming](#). It works nicely with a variety of other morphological variations of a word.

These strategies allow you to limit a single word's variability to a single root. We can, for example, reduce "singer," "singing," "sang," and "sang" to a singular version of the word "sing." We can quickly reduce the data space required and construct more powerful and robust NLP algorithms by doing this to all the terms in a document or text.

(3.5) *Keyword Extraction*: Keywords Extraction is one of the most important tasks in Natural Language Processing, and it is responsible for determining various methods for extracting a significant number of words and phrases from a collection of texts. All of this is done to summarise and assist in the relevant and well-organized organization, storage, search, and retrieval of content.

There are numerous keyword extraction algorithms

available, each of which employs a unique set of fundamental and theoretical methods to this type of problem. There are various types of NLP algorithms, some of which extract only words and others which extract both words and phrases. There are also NLP algorithms that extract keywords based on the complete content of the texts, as well as algorithms that extract keywords based on the entire content of the texts.

The following are some of the most prominent keyword extraction algorithms:

Text Rank: This algorithm operates on the same idea as Page Rank. Google uses this method to rank the importance of various websites on the internet.

Term Frequency – Inverse Document Frequency (TF-IDF): The full version of TF-IDF is Term Frequency–Inverse Document Frequency, which tries to better define the importance of a term in a document. Also, take into account the relationships between texts from the same corpus.

RAKE: RAKE stands for Rapid Automatic Keywords Extraction and is a type of NLP method. This can extract keywords and key phrases from a single document's content without taking into account other documents in the same collection.

(3.6) *Knowledge Graphs*: Knowledge graphs are a collection of three items: a subject, a predicate, and an entity that explain a method of storing information using triples.

The subject of approaches for extracting knowledge- getting ordered information from unstructured documents includes awareness graphs.

[Knowledge graphs](#) have recently become more popular, particularly when they are used by multiple firms (such as the Google Information Graph) for various goods and services.

Building a knowledge graph requires a variety of [NLP techniques](#) (perhaps every technique

covered in this article), and employing more of these approaches will likely result in a more thorough and effective knowledge graph.

(3.7) *Words Cloud*: Sometimes known as a tag cloud, is a data visualization approach. Words from a text are displayed in a table, with the most significant terms printed in larger letters and less important words depicted in smaller sizes or not visible at all.

Before applying other NLP algorithms to our dataset, we can utilize word clouds to describe our findings.

(3.8) *Named Entity Recognition*: Another significant technique for analyzing natural language space is named entity recognition. It's in charge of classifying and categorizing persons in unstructured text into a set of predetermined groups. This includes individuals, groups, dates, amounts of money, and so on.

There are two sub-steps to named entity recognition. Named Entity Identification (the identification of prospective NER algorithm candidates) and Named Entity Classification are two of these phases (assignment of candidates to one of the predefined categories)

(3.5) *Sentiments Analysis*: Sentiment analysis is the most often used NLP technique. Emotion analysis is especially useful in circumstances where consumers offer their ideas and suggestions, such as consumer polls, ratings, and debates on social media.

In emotion analysis, a three-point scale (positive/negative/neutral) is the simplest to create. In more complex cases, the output can be a statistical score that can be divided into as many categories as needed.

Both supervised and unsupervised algorithms can be used for sentiment analysis. The most frequent controlled model for interpreting sentiments is Naive Bayes.

A sentiment-labeled training corpus is required, from which a model can be trained and then utilized to define the sentiment. Naive Bayes isn't the only machine learning method that can be used; it can also employ random forest or gradient boosting.

III. RESULT AND DISCUSSION

MATLAB is used to implement the method. The method has been tested on a variety of scanned and printed document pictures. Various images/documents were considered, with minimal overlapping and fewer broken and connected characters. As predicted, the program delivered a less efficient text extraction with small details for handwritten notes with moderately blurred text.

The application is capable of identifying text from natural images as shown below:



Figure 7 Captured Image of a street Sign

Image to Speech Conversion Using Digital Image Processing



Figure 8 Applications correctly identifies the text

The application is capable of identifying handwritten text as shown below:




Figure 9 Captured Image of a handwritten text



Figure 10 Application detects the correct text
The application is capable of identifying text
form uploaded PDF as shown:
Rozelle Jain and Shantanu Das





Figure 12 Application detects the correct text from PDF file.

The intermediate text is presented sentence by phrase alongside the voice in this example.

Other features are available. The pitch is set to Microsoft Anna - United States, and the tempo is set to 0, which is the typical pace. The definition of the word "font" is looked up and shown. The system is tested using the methods outlined above. Testing is essential to offer information about the quality of the developed system. It determines if the system is fit for usage.

Test case	Description	Expected Result	Result
1.	Capture Blur or Low-Resolution Image from Camera	Error: "Text cannot be extracted, please retry"	Pass
2.	Give Incorrect Path to Upload Image	Error: "Image does not exist, please retry"	Pass
3.	Give Incorrect Path to Upload PDF File	Error: "File does not exist, please retry"	Pass
4.	Search for a non-existent word meaning	Pause/Stop recitation Error: "Incorrect spelling, please recheck"	Pass
5.	Start application, Capture Images from Webcam, Recite Text	Display text sentence wise and recite the same Provide options of Pause/Play, Stop, Save	Pass

REFERENCES

- [1] Archana A. Shinde, D. G. Chougule "Text Pre-processing and Text Segmentation for OCR" IJCSET, January 2012.
- [2] Benjamin Z. Yao, Xiong Yang, Liang Lin, MunWai Lee and Song-Chun Zhu, "I2T: Image Parsing to Text Description".
- [3] Bernard Gosselin, Faculté Polytechnique de Mons, Laboratoire de Théorie des Circuits.
- [4] Huizhong Chen¹, Sam S. Tsai¹, Georg Schroth, David M. Chen, Radek Grzeszczuk and Bernd
- [5] Jisha Gopinath, Aravind S, Pooja Chandran, Saranya S S, "Text to Speech Conversion System using OCR", International Journal of Emerging Technology and Advanced Engineering,

- [6] Itunuoluwasewon, Jelili Oyelade, Olufunke Oladipupo, "Design and Implementation of Text To Speech Conversion for Visually Impaired People", International Journal of Applied Information Systems (IJ AIS, 2014).
- [7] Yao Li and Huchuan Lu, "Scene Text Detection via Stroke Width", 21st International Conference on Pattern Recognition (ICPR 2012) November 11-15, 2012. Tsukuba, Japan.